

DELTA - Aquastrip® Primer

For priming of concrete, blockwork, brick, old bitumen coatings and most other (non solvent sensitive) substrates prior to the application of **Delta Membranes** Corner-Strip, self-adhesive membranes, tapes and liquid bitumen membranes.

DELTA - Aquastrip Primer:

- Is a rapid drying primer for Delta Membranes adhesives.
- Penetrates the surface of concrete joint faces so as to provide a water barrier.
- Dries to form a surface coating which seals the substrate/sealant interface and creates an adhesive bond.
- Provides a watertight joint between pre-cast concrete sections, which is flexible and resistant to internal and external hydrostatic pressure.
- Is resistant to sulphates, acids, alkalis, salts, grease, sewage, groundwater, micro-organisms and penetration by roots.
- Meets the performance requirements of BS EN 1917:2002.



Properties

Solvent	-	Petroleum spirit
Boiling range of solvent	-	130°C
Flash Point (DIN 51758)-		30°C
Density (DIN 51757)	-	approx 0,9g/cm ³
Solids content	-	approx 52%
Drying time	-	10 to 20 minutes depending on temperature and air movement
Coverage (average)	-	1 litre / 7 sq metres,
Hazardous goods class	-	Class 3, flammable

Application

- Application temperature -10°C to 50°C.
- Before use stir thoroughly in original container.
- Before application ensure that substrate is clean and dry.
- Application by brush
- After use close container firmly.
- Clean non-disposable brushes in white spirit.

Health and Safety (EU Directive 91/155/EEC)

Risk and Safety Clauses:

R10 Flammable.

S29 Do not allow the liquid to get into sewerage system.

S33 Take measures against electrostatic charging.

S43 Use powder fire extinguishing agents (not water) for extinguishing.

S51 If possible, work outdoors or in ventilated rooms.

(For further information refer to MSDS)

Units and Packing

Contents/packing	Dia. x height	gross weight	tins per pallet	pallet (length x width x height)
5 litre tin	182 x 220mm	5kg	120	1200 x 800 x 1110mm