

# Material Safety Data Sheet

**1.PRODUCT NAME:** **Delta Mastic**

---

## 2. HAZARD IDENTIFICATION

There are no ingredients in concentrations likely to constitute a hazard to health.

---

## 3. COMPOSITION

Homogeneous mixture of mineral filler, aqueous acrylic polymer, plasticiser, surfactants and fungicide.

HAZARDOUS INGREDIENT	CAS No.	EC No.	Weight %	Symbols	Risk Phrases
Isothiazoline			<1	Irritating to eyes & May Cause sensitisation by Skin contact	R36/R43

---

## 4. FIRST AID

CONTACT WITH SKIN:	Wash with plenty of soap and water. If irritation persists, obtain medical advice.
CONTACT WITH EYES:	Wash out with cold water for several minutes and seek medical advice.
INGESTION:	In case of ingestion of any material, drink water and seek medical attention immediately
INHALATION:	Remove casualty from exposure into fresh air.

---

## 5.FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	Foam, Foam Spray AFF, Dry Powder, Carbon Dioxide.
SPECIAL PROTECTIVE EQUIPMENT:	Full protective equipment. Toxic and irritant fumes may be produced.
COMBUSTION PRODUCTS:	Water, Carbon Dioxide, Carbon Monoxide, incompletely burned carbon products.

---

## 6.ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	Remove any source of ignition until all the material has been cleared.
ENVIRONMENTAL PRECAUTIONS:	Do not allow to enter public sewers and watercourses. If this cannot be avoided, inform the appropriate authority.
CLEAN-UP PROCEDURES	Small quantities of spilled material should be wiped up immediately with rags and the rags disposed of in a solid waste container. Larger quantities of material should be absorbed into sand, shovelled into buckets and taken to a safe open space for evaporation before disposal into normal solid waste containers.

---

## 7. HANDLING AND STORAGE

### HANDLING PRECAUTIONS

Ensure good ventilation and avoid breathing the vapour. Avoid contact with skin and eyes and do not swallow.

### STORAGE INFORMATION

Store in cool dry conditions away from direct sunlight or any other source of heat at temperatures below 25 °C and above 0 °C.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Wear protective clothing, including eye protection and PVC or synthetic / rubber gloves.  
Wash hands and exposed skin before meals and after work. Do not eat, drink or smoke whilst handling the product.  
Avoid breathing the vapour. Maintain good ventilation.

### EXPOSURE LIMITS

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Gun applied soft paste filled in cartridges. White & Brown	Oxidising Properties	None
Odour	Solvent	Vapour Pressure	No data
pH	7.8-8.3	Relative density	1.2 (25°C)
Boiling Point	Not Relevant	Bulk density	Not Relevant
Melting Point	Not Relevant	Volatile Content	13.0%
Flash Point	Not Relevant – water based	Solubility	Mixable with water when uncured
Autoignition temperature	No data	S.G	1.7
Explosive properties	No data	Other data	

## 10. STABILITY/REACTIVITY

Stable at normal ambient temperatures and under recommended handling and storage conditions.

## 11. TOXICOLOGICAL INFORMATION

EYE CONTACT:	May cause smarting and irritation.
SKIN CONTACT:	Prolonged contact will defat and dry skin leading to possible irritation and dermatitis.
INHALATION:	Prolonged inhalation of high vapour concentrations can cause headaches and nausea.
INGESTION:	May cause irritation of the mouth, throat and digestive system and eventual vomiting.

## 12. ECOLOGICAL INFORMATION

DEGRADABILITY: Not biodegradable.  
ECOTOXICITY: Aquatic and terrestrial ecotoxicity not known.

---

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations e.g: incineration or landfill.

---

## 14. TRANSPORT INFORMATION

UN NO. Not Applicable  
No special packaging or labelling requirements for Road, Rail, Sea or Air Transport.

---

## 15. REGULATORY INFORMATION

This type of product is determined as not being dangerous for supply.

---

## 16. OTHER INFORMATION

The information contained in this data sheet is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

*Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.*