



The Delta Foul V3 is a packaged pump station designed to collect foul water.

Typically, the Foul V3 would be used to collect and discharge foul water from a basement fitted with a bathroom and utility room. This pump station is not designed to collect ground water from a cavity membrane system (see Delta Dual V3 - DMS 164). For kitchen applications we recommend fitting a grease trap prior to the pump station.

info@deltamembranes.com

www.deltamembranes.com

01992 523 523



BENEFITS

- The Foul V₃ pump station package includes chamber, all internal pipework and a powerful D10 foul vortex Pump
- Suitable for Flood Resilience
- Suitable for new, existing and retrofit basement projects
- Service Plans available through our pump partners if required
- Suitable for residential, commercial and heritage buildings



SPECIFICATION

- NBS Specification R18 (Clause 310) Pumping Stations and Pressure Pipelines
- BS 8102:2009 Type C Drained Protection



ASSOCIATED PRODUCTS

- AlertMaxx2
- Delta HLA
- Powermaxx XL

PRODUCT DATA SHEET

DELTA V₃ FOUL

Product Code: DMS165

TECHNICAL DATA

Chamber	Foul V ₃
Chamber Material	High Density Polyethylene
Volume Below Inlets	137L
Volume Total	273L
Fixed Inlets	3 x 110/160mm
Cable Duct	50mm
Discharge Connection	2" / 50mm BSP Class C
Discharge Pipework	2" / 50mm BSP Class C
Internal Pipework	2" / 50mm BSP Class C
Cable Duct Pipework	2" / 50mm White Waste Pipe
Vent Pipework	2" / 50mm White Waste Pipe

PRODUCT DATA SHEET

DELTA V₃ FOUL

Product Code: DMS165

TECHNICAL DRAWING

Standard Delta V₃ Foul

