

DELTA ROOF GUARD PU SOLVENT

Delta Roof Guard PU Solvent can be used for viscosity adjustments and tool cleaning

Solvent mixture, fully compatible with the solvent-based Delta Roof Guard product range, suitable for in-situ viscosity adjustments and tool cleaning. Best suited Delta Roof Guard products are, among others:

- Delta Roof Guard QC
- Delta Roof Guard Colodur



AS THINNER

Pour the solvent into the original product to be thinned or in the application container. Mix with a low-speed stirrer, avoiding excessive bubble formation. Use the product normally or keep it in a suitable container. It is not recommended to use more than a 5% of solvent for thinning without checking for possible retraction defects during curing. The following table gives approximate values for viscosity decreasing in Delta Roof Guard samples.

FOR TOOL CLEANING

Dip the tools into a suitable container filled with Delta Roof Guard PU Solvent. Keep them cleaning until waste dispersion and clean thoroughly the tool immediately afterwards. If exposed to evaporation without cleaning, the dispersed residues will deposit again onto the tool and eventually harden. Delta Roof Guard PU Solvent cannot clean hardened residues. Caution: Delta Roof Guard PU Solvent can damage some plastics.

SAFETY

Delta Roof Guard PU Solvent contains flammable solvent. Take all precautions as described in the Material Safety Data Sheet.

ENVIRONMENTAL PRECAUTIONS

Empty containers must be handled taking the same precautions as if they were full. Containers must be considered as hazardous waste, to be transferred to an authorised waste manager.

OTHER INFORMATION

Disclaimer: All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.

