



Description

Delta Amphibia Safety Tape is a secure, durable waterproof adhesive tape used for sealing and connecting Delta Amphibia membranes at joints and overlaps, and/or sealing around service penetrations and foundation piles.

Delta Amphibia is a pre- and post-applied waterproofing membrane which can be installed horizontally and vertically in a Type A waterproofing application.

Fields of Application

- Sealing Delta Amphibia Membranes
- Sealing Service Penetrations
- Sealing Foundation Piles
- External Corners
- Internal Corners

Specification

- BS 8102:2022 Protection of below ground structures against water ingress. Code of practice.
- NBS J40 / 130 – Flexible Sheet Tanking / waterproofing

Product Details

DMS 1002

Associated Products

- Delta Amphibia Membranes
- Delta Amphibia AKTI-VO 201
- Delta Amphibia BI Mastic
- Delta Amphibia Pressure Corner 90°
- Delta Amphibia Pressure Line

Other Information

All data and information contained in these Product/Technical Data Sheets is up-to-date and correct as at the date of issue. The information given is suggested as guidance and should only be used for evaluating your specific application. Delta Membrane Systems Limited cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. The information contained in these Product/Technical Data Sheets should not be considered a warranty, expressed, or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose. In no event shall Delta Membrane Systems Limited be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory. When in doubt, contact Delta's Technical Team on 01992 523 523.

Technical Data

Delta Amphibia Safety Tape	
DMS	1002
Colour	White
Width	60mm
Length	25m
Material	Adhesive tape based on acrylic/acid/ester copolymer
Safety	Use protective gloves to avoid contact with skin
Contents/Packaging	1 Roll

The data reported are obtained in the laboratory at +20°C and 60% R.H. (relative humidity).

Adequate training is required before industrial or professional use.

